



Consolite Technology Specification Sheet

Part No: CTL-C020

Part name: Filter Glass, Colour LCD Monitor


The filter glass is of absorption type and achieves the NVIS radiance requirements of MIL-STD-3009 (Class B) and DO-275. The material can work at thicknesses down to 1mm for use in thin strip form for individual edge illuminating CCFLs, or at up to 2mm for use in sheet form across the front of an LCD. In the latter case an anti-reflection coating can be provided on one or both faces to minimise reflections and to optimise transmission.

Performance figures are quoted for a typical full colour LCD cockpit display, measured in white and red areas, each dimmed as close to 0.5fL as possible, for an uncoated filter at both thicknesses. Exact figures may vary.

Typical performance

		NR _B @ 0.5fL	Chromaticity		Photopic transmission
			u'	v'	
1mm	White	1.9E-9	.165	.458	78%
	Red	7.7E-9	.342	.494	58%
2mm	White	3.3E-10	.148	.452	68%
	Red	1.9E-9	.308	.480	40%

Spectral Transmission at 1mm thickness



Consolite Technology Limited, St. Martins Business Park, Bells Lane, Zeals, Wiltshire, BA12 6LY, UK

Tel: +44 (0)1747 840900
e-mail: sales@consolite.co.uk

Fax: +44 (0)1747 841500
Web: www.consolite.co.uk